VAUXHALL TRADE CLUB TECHNICAL DATA SHEET





Typical Inspection Data:	
Density @ 20 °C	0.844 g/cm³
Viscosity (a) 100 °C	8.5 cSt
Viscosity @ 40 °C	45 cSt
Viscosity Index	169
Viscosity CCS @ -35 °C	6000 cP
T.B.N.	7.9 mg KOH/g
Sulphated Ash Mass	0.8%
Zinc	0.10%
Calcium	0.13%
Phosphorus	0.08%
Colour	Brown
Flash Point	230 °C
Pour Point	-42 °C

Specifications:

API SN ILSAC GF-4, GF-5

VAUXHALL TRADE CLUB

FS 0W-20

Fully Synthetic Fuel Economy Engine Oil

Description:

Vauxhall Trade Club FS OW-20 is a fully synthetic multigrade engine oil designed for use in the petrol engines of many modern passenger cars.

It is formulated with premium fully synthetic base stocks and performance additives which enable it to cope with the demanding conditions found in modern engines.

Vauxhall Trade Club FS OW-20 is designed for optimum fuel efficiency without compromising on engine protection. It ensures components are kept clean and wear-free in all conditions, even at extreme temperatures.

Features & Benefits:

- Top-tier engine wear protection
- Excellent low temperature properties
- Provides high levels of engine cleanliness

Application:

Vauxhall Trade Club FS OW-20 is recommended primarily for many of the latest Honda, Toyota, Mazda and Suzuki petrol engines. It can be used where any of the following performance specifications and an SAE OW20 viscosity grade is required.

Health & Safety:

Please refer to the relevant health and safety data sheet. Copies are available to Trade Club members at www.tradeclub.co.uk

Part Numbers/ Pack Sizes:

- 199L UKTOBA12
- 20L UKTOTW12
- 5L UKTOFL12



Created: 19/07/18 Updated: 16 January 2019 11:06 am



www.tradeclub.co.uk

3780/5