



Typical Inspection Data:

| | |
|------------------------|-------------------------|
| Density @ 20 °C | 0.845 g/cm ³ |
| Viscosity @ 100 °C | 10.0 cSt |
| Viscosity @ 40 °C | 55 cSt |
| Viscosity Index | 166 |
| Viscosity CCS @ -30 °C | 4500 cP |
| T.B.N. | 6.0 mg KOH/g |
| Sulphated Ash Mass | 0.49% |
| Zinc | 0.07% |
| Calcium | 0.12% |
| Phosphorus | 0.05% |
| Colour | Brown |
| Flash Point | 230 °C |
| Pour Point | -42 °C |

Specifications:

ACEA C1 Ford WSS-M2C934-B;
STJLR 03.5005

TRADE CLUB

www.tradeclub.co.uk

VAUXHALL TRADE CLUB

C1 5W-30

Fully Synthetic Low SAPS Engine Oil

Description:

Vauxhall Trade Club 5W-30 C1 is a fully synthetic multigrade engine oil designed for use in light duty diesel and petrol engines found in a number of passenger cars and vans. In particular Trade Club 5W-30 C1 is designed for use in vehicles fitted with exhaust after treatment systems where its low SAPS (sulphated ash, phosphorus and sulphur) levels ensure the correct operation of devices such as diesel particulate filters and catalytic converters.

Features & Benefits:

- Fuel efficient multigrade
- Long drain intervals
- Excellent low temperature properties
- Very high standards of engine cleanliness

Application:

Trade Club 5W-30 C1 is recommended for a number of the latest diesel and petrol engines, including turbocharged, in passenger cars and light commercial vehicles. Typical manufacturers include Mazda, Jaguar, Land Rover and Toyota.

Health & Safety:

Please refer to the relevant health and safety data sheet. Copies are available to Trade Club members at www.tradeclub.co.uk

Part Numbers/ Pack Sizes:

- 199L – UKTOBA10
- 20L – UKTOTW10
- 5L – UKTOFL10



Created: 19/07/18

Updated: 16 January 2019 11:16 am



VAUXHALL