



## Typical Inspection Data:

Density @ 20 °C	0.845 g/cm <sup>3</sup>
Viscosity @ 100 °C	11.9 cSt
Viscosity @ 40 °C	70 cSt
Viscosity Index	167
Viscosity CCS @ -30 °C	5500 cP
T.B.N.	8.0 mg KOH/g
Sulphated Ash Mass	0.8%
Zinc	0.10%
Calcium	0.19%
Phosphorus	0.08%
Colour	Brown
Flash Point	230 °C
Pour Point	-36 °C

## Specifications:

ACEA C2, API SN

**TRADE CLUB**

[www.tradeclub.co.uk](http://www.tradeclub.co.uk)

## VAUXHALL TRADE CLUB

### C2 5W-30

### Fully Synthetic Low SAPS Engine Oil

#### Description:

Vauxhall Trade Club C2 5W-30 is a low SAPS (Sulphated Ash, Phosphorus and Sulphur) fully synthetic, multi grade engine oil, specially formulated to meet the superior performance and fuel efficiency requirements of modern engines that require low viscosity oils for petrol and diesel applications. Vauxhall Trade Club C2 5W-30 has been developed for use in Euro IV and V compliant vehicles with DPF after treatment devices.

#### Features & Benefits:

- Improved fuel economy benefits
- Excellent sludge control
- Compatible with diesel particulate filters
- Low volatility

#### Application:

Vauxhall Trade Club C2 5W-30 is recommended for use in passenger cars and light commercial vehicles both with and without diesel particulate filters. It can be used in both petrol and diesel engines where the following specifications are required.

#### Health & Safety:

Please refer to the relevant health and safety data sheet. Copies are available to Trade Club members at [www.tradeclub.co.uk](http://www.tradeclub.co.uk)

#### Part Numbers/ Pack Sizes:

- 199L - UKTOBA03
- 20L - UKTOTW03
- 5L - UKTOFL03



Created: 19/07/18

Updated: 16 January 2019 9:15 am



**VAUXHALL**