VAUXHALL TRADE CLUB TECHNICAL DATA SHEET





Typical Inspection Data:	
Density @ 20 °C	0.850 g/cm³
Viscosity @ 100 °C	11.7 cSt
Viscosity @ 40 °C	68 cSt
Viscosity Index	170
Viscosity CCS @ -30 °C	5700 cP
T.B.N.	8.6 mg KOH/g
Sulphated Ash Mass	0.8%
Zinc	0.10%
Calcium	0.17%
Phosphorus	0.09%
Colour	Brown
Flash Point	230 °C
Pour Point	-36 °C

Specifications:

ACEA C3 VW 504 00, 507 00; BMW LL-04; Porsche C30; MB 229.31, 229.51

TRADE CLUB

www.tradeclub.co.uk

VAUXHALL TRADE CLUB C3 MX 5W-30

Fully Synthetic Low Saps Engine Oil

Description:

Vauxhall Trade Club C3 MX 5W-30 is a low SAPS (Sulphated Ash, Phosphorus and Sulphur) fully synthetic, multigrade engine oil designed for use in the latest technology engines, including those fitted with exhaust gas after treatment devices. Vauxhall Trade Club C3 MX 5W-30 meets the requirements of VW Standards 504.00 and 507.00 and can be used in most of their engine designs.

Features & Benefits:

- Outstanding levels of engine cleanliness
- · Long drain intervals
- Compatible with diesel particulate filters
- Low volatility

Application:

Vauxhall Trade Club C3 MX 5W-30 is recommended for use in passenger cars and light commercial vehicles both with and without diesel particulate filters. It can be used in both petrol and diesel engines where the following specifications are required.

Health & Safety:

Please refer to the relevant health and safety data sheet. Copies are available to Trade Club members at www.tradeclub.co.uk

Part Numbers/ Pack Sizes:

- 199L UKTOBA02
- 20L UKTOTW02
- 5L UKTOFL02



Created: 19/07/18 Updated: 11 January 2019 3:46 pm

