VAUXHALL TRADE CLUB TECHNICAL DATA SHEET





Typical Inspection Data:	
Density @ 20 °C	0.848 g/cm³
Viscosity @ 100 °C	9.9 cSt
Viscosity @ 40 °C	55 cSt
Viscosity Index	166
Viscosity CCS @ -30 °C	4000 cP
T.B.N.	10.0 mg KOH/g
Sulphated Ash Mass	1.1%
Zinc	0.12%
Calcium	0.26%
Phosphorus	0.10%
Colour	Brown
Flash Point	230 °C
Pour Point	-36 °C

Specifications:

ACEA A5/B5. API SL CF

Ford WSS-M2C913-A/WSS-M2C913-B/WSS-M2C913-C/WSS-M2C913-D; STJLR 03.5003; RN0700

TRADE CLUB

www.tradeclub.co.uk

VAUXHALL TRADE CLUB FE 5W-30

Fully Synthetic Engine Oil Recommended For Modern Ford Engines

Description:

Vauxhall Trade Club FE 5W-30 is a fully synthetic multigrade engine oil specially formulated to meet the superior performance and fuel efficiency requirements of modern engines requiring low viscosity oils. Enhanced oil flow and film strength give essential protection during start-up and advanced additive technology ensures maximum engine protection even under arduous conditions.

Features & Benefits:

- Fuel efficient multigrade
- · Long drain intervals
- Excellent low temperature fluidity.

Application:

Vauxhall Trade Club 5W-30 FE is recommended for the majority of Ford petrol and diesel engines, including turbocharged, in passenger and light commercial vehicles. Also recommended where any of the following specifications and a 5W-30 viscosity grade are required.

Health & Safety:

Please refer to the relevant health and safety data sheet. Copies are available to Trade Club members at www.tradeclub.co.uk

Part Numbers/ Pack Sizes:

- 199L UKTOBA04
- 20L UKTOTW04
- 5L UKTOFL04



Created: 19/07/18 Updated: 15 January 2019 4:17 pm

