



Typical Inspection Data:

Density @ 20 °C	0.852 g/cm ³
Viscosity @ 100 °C	10.4 cSt
Viscosity @ 40 °C	58 cSt
Viscosity Index	165
Viscosity CCS @ -30 °C	4600 cP
T.B.N.	10.0 mg KOH/g
Sulphated Ash Mass	1.0%
Zinc	0.11%
Calcium	0.32%
Phosphorus	0.11%
Colour	Brown
Flash Point	230 °C
Pour Point	-39 °C

Specifications:
ACEA A5/B5, API SL

TRADE CLUB
www.tradeclub.co.uk

VAUXHALL TRADE CLUB

SS 5W-30

Semi-Synthetic Motor Oil For Older Ford Engines

Description:

Vauxhall Trade Club 5W-30 SS is a semi-synthetic, multigrade engine oil, specially formulated to meet the superior performance and fuel efficiency requirements of modern engines requiring low viscosity oils. Enhanced oil flow gives essential protection during start-up and advanced additive technology provides long term benefits including reduced wear on critical components.

Features & Benefits:

- Fuel efficient multigrade formulation
- Good thermal stability
- Excellent low temperature properties
- Low viscosity gives excellent protection for cold starting

Application:

Vauxhall Trade Club 5W-30 SS is recommended for petrol and diesel engines in passenger cars and light commercial vehicles. It is particularly suitable for use in many older Ford vehicles as well as other manufacturers such as Land Rover where any of the following specifications and a 5W-30 viscosity grade are required.

Health & Safety:

Please refer to the relevant health and safety data sheet. Copies are available to Trade Club members at www.tradeclub.co.uk

Part Numbers/ Pack Sizes:

- 199L – UKTOBA06
- 20L – UKTOTW06
- 5L – UKTOFL06



Created: 19/07/18
Updated: 17 January 2019 3:44 pm



VAUXHALL