



## Typical Inspection Data:

Density @ 20 °C	0.850 g/cm <sup>3</sup>
Viscosity @ 100 °C	13.5 cSt
Viscosity @ 40 °C	78 cSt
Viscosity Index	160
Viscosity CCS @ -30 °C	6000 cP
T.B.N.	8.0 mg KOH/g
Sulphated Ash Mass	0.8%
Zinc	0.10%
Calcium	0.18%
Phosphorus	0.09%
Colour	Brown
Flash Point	230 °C
Pour Point	-39 °C

## Specifications:

ACEA C3, API SN; MB 229.31, MB 226.5; VW 502 00, VW 505 01; Porsche A40; Ford WSS-M2C917-A

**TRADE CLUB**

[www.tradeclub.co.uk](http://www.tradeclub.co.uk)

## VAUXHALL TRADE CLUB

### C3 5W-40

### Fully Synthetic Low SAPS Engine Oil

#### Description:

Vauxhall Trade Club C3 5W-40 is a low SAPS (Sulphated Ash, Phosphorus and Sulphur) fully synthetic multigrade engine oil designed for use in the latest technology engines, including those fitted with exhaust gas after treatment devices. It has a broad range of applications and genuine long oil drain capabilities.

#### Features & Benefits:

- Ensures lubricant performance over extended drain intervals
- Very high standards of engine cleanliness
- Exceptional long term anti-wear and oxidation stability
- Excellent high and low temperature performance

#### Application:

Vauxhall Trade Club C3 5W-40 is particularly suited to vehicles equipped with anti-pollution systems such as diesel particulate filters where its low SAPS levels will greatly prolong the lifetime of the filter. It is also ideally suited to VW PD (Pumpe Düse) engines.

#### Health & Safety:

Please refer to the relevant health and safety data sheet. Copies are available to Trade Club members at [www.tradeclub.co.uk](http://www.tradeclub.co.uk)

#### Part Numbers/ Pack Sizes:

- 199L – UKTOBA09
- 20L – UKTOTW09
- 5L – UKTOFL09



Created: 19/07/18

Updated: 4 February 2019 3:24 pm



**VAUXHALL**