VAUXHALL TRADE CLUB TECHNICAL DATA SHEET





Typical Inspection Data:	
Density @ 20 °C	0.853 g/cm³
Viscosity @ 100 °C	13.5 cSt
Viscosity @ 40 °C	80 cSt
Viscosity Index	170
Viscosity CCS @ -30 °C	6000 cP
T.B.N.	10.0 mg KOH/g
Sulphated Ash Mass	1.1%
Zinc	0.12%
Calcium	0.26%
Phosphorus	0.10%
Colour	Brown
Flash Point	230 °C
Pour Point	-39 °C

Specifications:

ACEA A3/B4, API SL VW 502 00, 505 00; MB 229.3; BMW LL-98; RN 0700/0710

VAUXHALL TRADE CLUB

FS 5W-40

Fully Synthetic Passenger Car Engine Oil

Description:

Vauxhall Trade Club FS 5W-40 is a fully synthetic, multigrade engine oil specially formulated to offer long term durability and engine protection in a wide variety of conditions. It is recommended for use in petrol and diesel engines in passenger cars and vans where its advanced additive technology provides significant benefits.

Features & Benefits:

- Excellent anti-wear protection
- Long drain intervals
- Excellent low temperature properties
- High levels of engine cleanliness

Application:

Vauxhall Trade Club FS 5W-40 is recommended for the latest petrol and diesel engines, including turbocharged and supercharged versions, in passenger cars and light commercial vehicles. It is recommended where any of the following specifications and a 5W-40 viscosity grade are required.

Health & Safety:

Please refer to the relevant health and safety data sheet. Copies are available to Trade Club members at www.tradeclub.co.uk

Part Numbers/ Pack Sizes:

- 199L UKTOBA07
- 20L UKTOTW07

Updated: 11 January 2019 2:42 pm

• 5L – UKTOFL07

Created: 19/07/18



VAUXHALL

TRADE CLUB www.tradeclub.co.uk