



SAFETY DATA SHEET TRADE CLUB 75W-90 FS AXLE

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name TRADE CLUB 75W-90 FS AXLE
Product number UKTOGF04, UKTOGA04, UKTOGB04

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Gear oil.

1.3. Details of the supplier of the safety data sheet

Supplier
Vauxhall Trade Club
Griffin House, UK1-102-303, Osborne Road, Luton, Bedfordshire, LU1 3YT
0844 840 8289

1.4. Emergency telephone number

Emergency telephone 0844 840 8289

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified
Health hazards Eye Irrit. 2 - H319 Skin Sens. 1 - H317
Environmental hazards Aquatic Chronic 3 - H412

2.2. Label elements

Pictogram



Signal word Warning

Hazard statements
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H412 Harmful to aquatic life with long lasting effects.

TRADE CLUB 75W-90 FS AXLE

Precautionary statements	P261 Avoid breathing vapour/ spray.
	P264 Wash contaminated skin thoroughly after handling.
	P272 Contaminated work clothing should not be allowed out of the workplace.
	P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
	P302+P352 IF ON SKIN: Wash with plenty of water.
	P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P321 Specific treatment (see medical advice on this label).
	P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.
	P337+P313 If eye irritation persists: Get medical advice/ attention.
	P362+P364 Take off contaminated clothing and wash it before reuse.
	P501 Dispose of contents/ container in accordance with national regulations.
P101 If medical advice is needed, have product container or label at hand.	
P102 Keep out of reach of children.	

Contains	REACTION PRODUCTS OF BIS(4-METHYLPENTAN-2-YL)DITHIOPHOSPHORIC ACID WITH PHOSPHORUS OXIDE, PROPYLENE OXIDE AND AMINES, C12-14 ALKYL (BRANCHED), REACTION PRODUCTS OF 1,3,4-THIADIAZOLIDINE-2,5-DITHIONE, FORMALDEHYDE AND PHENOL, HEPTYL DERIVS.".
-----------------	---

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC. <3% DMSO EXTRACT		1-<2.5%
CAS number: 64742-53-6	EC number: 265-156-6	REACH registration number: 01-2119480375-34-0000
Classification Asp. Tox. 1 - H304	Classification (67/548/EEC or 1999/45/EC) Xn;R65.	
REACTION PRODUCTS OF BIS(4-METHYLPENTAN-2-YL)DITHIOPHOSPHORIC ACID WITH PHOSPHORUS OXIDE, PROPYLENE OXIDE AND AMINES, C12-14 ALKYL (BRANCHED)		0.5-<1%
CAS number: —	EC number: 931-384-6	REACH registration number: 01-2119493620-38-0000
Classification Acute Tox. 4 - H302 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411	Classification (67/548/EEC or 1999/45/EC) Xn;R22. Xi;R41. N;R51/53. R43.	

TRADE CLUB 75W-90 FS AXLE

OLEYLAMINE	0.5-<1%
CAS number: 112-90-3	EC number: 204-015-5
M factor (Acute) = 1	M factor (Chronic) = 1
Classification Acute Tox. 4 - H302 Skin Corr. 1B - H314 Eye Dam. 1 - H318 STOT SE 3 - H335 STOT RE 2 - H373 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410	Classification (67/548/EEC or 1999/45/EC) Xn;R22,R48/22. C;R34. Xi;R37. N;R50/53.
REACTION PRODUCTS OF 1,3,4-THIADIAZOLIDINE-2,5-DITHIONE, FORMALDEHYDE AND PHENOL, HEPTYL DERIVS."	0.1-<0.3%
CAS number: —	EC number: 939-460-0
	REACH registration number: 01-2119971727-23-0000
Classification Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Aquatic Chronic 3 - H412	Classification (67/548/EEC or 1999/45/EC) Xi;R38,R41. R43,R52/53.
TOLUENE	0.001 - <0.1%
CAS number: 108-88-3	EC number: 203-625-9
	REACH registration number: 01-2119471310-51-0000
Classification Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Repr. 2 - H361d STOT SE 3 - H336 STOT RE 2 - H373 Asp. Tox. 1 - H304	Classification (67/548/EEC or 1999/45/EC) F; R11. Xn; R65, R48/20/21/22. Xi; R38. Repr. Cat. 3 R63. R67

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition comments This product does not contain any hazardous ingredients, or ingredients with national workplace exposure limits.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Get medical attention if any discomfort continues. Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
Inhalation	If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
Ingestion	Contact physician if larger quantity has been consumed. Rinse mouth thoroughly with water.

TRADE CLUB 75W-90 FS AXLE

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation persists after washing.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Do not rub eye.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the length of exposure. Effects may be delayed. Keep affected person under observation.

Inhalation May cause an asthma-like shortness of breath. Vapours may cause headache, fatigue, dizziness and nausea.

Ingestion May cause discomfort if swallowed. May cause stomach pain or vomiting. May cause nausea, headache, dizziness and intoxication.

Skin contact Prolonged or repeated contact with skin may cause irritation, redness and dermatitis. Allergic rash.

Eye contact May cause temporary eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. If in doubt, get medical attention promptly.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with the following media: Foam, carbon dioxide or dry powder. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Fire creates: Carbon monoxide (CO). Carbon dioxide (CO₂). No unusual fire or explosion hazards noted.

Hazardous combustion products Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of carbon.

5.3. Advice for firefighters

Special protective equipment for firefighters Leave danger zone immediately.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Follow precautions for safe handling described in this safety data sheet. Avoid inhalation of vapours. Avoid contact with eyes and prolonged skin contact. Provide adequate ventilation. In case of spills, beware of slippery floors and surfaces.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground. Collect and dispose of spillage as indicated in Section 13.

6.3. Methods and material for containment and cleaning up

TRADE CLUB 75W-90 FS AXLE

Methods for cleaning up

Stop leak if possible without risk. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Provide adequate ventilation. Contain spillage with sand, earth or other suitable non-combustible material. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet. Collect and dispose of spillage as indicated in Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using the product. Avoid the formation of mists. Provide adequate ventilation. Avoid contact with skin and eyes. Always remove oil with soap and water or skin cleaning agent, never use organic solvents. Do not use oil-contaminated clothing or shoes, and do not put rags moistened with oil into pockets.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Keep containers upright. Store in tightly-closed, original container.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

No exposure limits known for ingredient(s).

TOLUENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 191 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 384 mg/m³

Sk

WEL = Workplace Exposure Limit

Sk = Can be absorbed through skin.

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

TRADE CLUB 75W-90 FS AXLE

Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Nitrile rubber. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended.
Other skin and body protection	Wear suitable protective clothing as protection against splashing or contamination.
Hygiene measures	Wash contaminated clothing before reuse. Wash promptly with soap and water if skin becomes contaminated.
Respiratory protection	No specific recommendations.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Clear liquid.
Colour	Brown.
Odour	Oil-like.
pH	Scientifically unjustified.
Melting point	Not determined.
Initial boiling point and range	>250°C @
Flash point	204°C
Evaporation rate	Not determined.
Upper/lower flammability or explosive limits	Not determined.
Vapour pressure	Not determined.
Vapour density	Not determined.
Relative density	0.883 g/cm ³ @ 20°C
Solubility(ies)	Insoluble in water.
Partition coefficient	Not determined.
Auto-ignition temperature	Not determined.
Decomposition Temperature	Not determined.
Viscosity	100 cSt @ 40°C

9.2. Other information

Other information	None.
--------------------------	-------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
-------------------	---

10.2. Chemical stability

Stability	No particular stability concerns.
------------------	-----------------------------------

10.3. Possibility of hazardous reactions

TRADE CLUB 75W-90 FS AXLE

Possibility of hazardous reactions Not applicable.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects No information available.

Ingestion May cause discomfort if swallowed.

Skin contact Prolonged and frequent contact may cause redness and irritation.

Eye contact May cause temporary eye irritation.

SECTION 12: Ecological Information

Ecotoxicity The product contains a substance which is harmful to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

12.1. Toxicity

Toxicity Not considered toxic to fish.

Acute toxicity - fish Not available.

Acute toxicity - aquatic invertebrates Not available.

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

12.4. Mobility in soil

Adsorption/desorption coefficient Not available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects Not available.

TRADE CLUB 75W-90 FS AXLE

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste is classified as hazardous waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods Confirm disposal procedures with environmental engineer and local regulations.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations EH40/2005 Workplace exposure limits.

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision date 28/01/2016

TRADE CLUB 75W-90 FS AXLE

Revision	9
Supersedes date	20/05/2015
SDS number	32331
SDS status	Approved.
Risk phrases in full	<p>Not classified.</p> <p>R10 Flammable.</p> <p>R11 Highly flammable.</p> <p>R20 Harmful by inhalation.</p> <p>R22 Harmful if swallowed.</p> <p>R34 Causes burns.</p> <p>R36/37/38 Irritating to eyes, respiratory system and skin.</p> <p>R38 Irritating to skin.</p> <p>R41 Risk of serious damage to eyes.</p> <p>R43 May cause sensitisation by skin contact.</p> <p>R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.</p> <p>R50 Very toxic to aquatic organisms.</p> <p>R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.</p> <p>R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.</p> <p>R63 Possible risk of harm to the unborn child.</p> <p>R65 Harmful: may cause lung damage if swallowed.</p> <p>R67 Vapours may cause drowsiness and dizziness.</p>
Hazard statements in full	<p>H225 Highly flammable liquid and vapour.</p> <p>H302 Harmful if swallowed.</p> <p>H304 May be fatal if swallowed and enters airways.</p> <p>H314 Causes severe skin burns and eye damage.</p> <p>H315 Causes skin irritation.</p> <p>H317 May cause an allergic skin reaction.</p> <p>H318 Causes serious eye damage.</p> <p>H335 May cause respiratory irritation.</p> <p>H336 May cause drowsiness or dizziness.</p> <p>H361d Suspected of damaging the unborn child.</p> <p>H373 May cause damage to organs through prolonged or repeated exposure.</p> <p>H400 Very toxic to aquatic life.</p> <p>H410 Very toxic to aquatic life with long lasting effects.</p> <p>H411 Toxic to aquatic life with long lasting effects.</p> <p>H412 Harmful to aquatic life with long lasting effects.</p> <p>EUH208 Contains REACTION PRODUCTS OF BIS(4-METHYLPENTAN-2-YL)DITHIOPHOSPHORIC ACID WITH PHOSPHORUS OXIDE, PROPYLENE OXIDE AND AMINES, C12-14 ALKYL (BRANCHED), REACTION PRODUCTS OF 1,3,4-THIADIAZOLIDINE-2,5-DITHIONE, FORMALDEHYDE AND PHENOL, HEPTYL DERIVS.". May produce an allergic reaction.</p>