

# **Technical Data Sheet**



Typical Inspection Data:	
Density @ 20°C	0.862 g/cm3
Viscosity @ 100°C	14.1 cSt
Viscosity @ 40°C	96 cSt
Viscosity Index	150
Viscosity CCS @ -25°C	6000 cP
T.B.N.	10.0 mg KOH/g
Sulphated Ash Mass	1.30%
Zinc	0.12%
Calcium	0.30%
Phosphorus	0.11%
Colour	Brown
Flash Point	230°C
Pour Point	-39°C

## A3/B4 10W-40

### High performance motor oil

#### Specifications:

#### ACEA A3/B4; API SN/CF

#### **Product Features:**

- Semi Synthetic based engine oil.
- High performance.
- For petrol and diesel engines without particle filters.

#### Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

#### Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Updated: 16/07/2020 (10:16)

PSA Automobiles SA, 2-10 Boulevard de l'Europe, 78300, Poissy, France. Tel: +33 1 61 45 45 45 www.eurorepar.com