

Technical Data Sheet



Typical Inspection Data: 0.850 g/cm3 Density @ 20°C Viscosity @ 100°C 14.5 cSt Viscosity @ 40°C 89 cSt Viscosity Index 170 Viscosity CCS @ -30°C 6000 cP T.B.N. 10.0 mg KOH/g Sulphated Ash Mass 1.10% Zinc 0.12% 0.30% Calcium Phosphorus 0.10% Colour Brown Flash Point (Closed Cup) 210°C Pour Point -39°C

A3/B4 5W-40

Synthetic technology engine oil

Specifications:

ACEA A3/B4; API SN/CF

Meets requirements of: VW 502 00, VW 505 00; MB 229.3; RN0700, RN0710

Product Features:

- Synthetic Technology Engine Oil.
- Very High Performance.
- For petrol and diesel engines (multi-valves, turbo, with or without catalytic converter).

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Updated: 16/07/2020 (10:16)