



EUROREPAR

# Technical Data Sheet



## ATF FSDCT

Oil for semi automatic transmissions

### Specifications:

Suitable for use in applications requiring: VW G 052 182 A2 or A6 (fluid); BMW Drivelogic 7-speed (Getrag) DCTF-1

### Product Features:

- Dual Clutch Transmission Fluid.
- High Performance. For use in the widest range of vehicle makes fitted with DSG or DCT wet transmissions.

### Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

### Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

### Typical Inspection Data:

Density @ 20°C	0.840 g/cm <sup>3</sup>
Viscosity @ 100°C	7.3 cSt
Viscosity @ 40°C	36 cSt
Phosphorus	0.02%
Colour	Brown
Pour Point	-36°C

Updated: 16/07/2020 (10:16)

PSA Automobiles SA, 2-10 Boulevard de l'Europe, 78300, Poissy, France.

Tel: +33 1 61 45 45 45 [www.eurorepar.com](http://www.eurorepar.com)