



EUROREPAR

Technical Data Sheet



ATF FSDX 6

Oil for automatic transmission

Specifications:

Suitable for use in applications requiring: Nissan Matic J, Nissan Matic D; Special ATF Honda ATF-Z1; Volvo 1161540; VW G 052 162, VW G 055 540; ZF-11A, ZF-11B; GM 1940771; Allison C-4; JWS 3309, JWS 3324 (ATF WS); LT71141; Mercon; ATF, Mercon LV; ATF, Mercon SP; ATF, Mercon V; SP-II; ATF, SP-III; ATF; Toyota Type T-II, Toyota Type T-IV; Chrysler MS 7176E (ATF +3), Chrysler MS 9602 (ATF +4); Dexron® II, Dexron® II D, Dexron® IIE, Dexron® IIE + Mercon, Dexron® III, Dexron® III (G), Dexron® (H), Dexron® III + Alison C-4, Dexron® III + Mercon, Dexron® VI; Ford ESP-M2C166-H, Ford M2C138-CJ, Ford WSS-M2C202-B, MB 236.10, MB 236.6, MB 236.7, MB 236.9

Typical Inspection Data:

Density @ 20°C	0.840 g/cm ³
Viscosity @ 100°C	6.4 cSt
Viscosity @ 40°C	33 cSt
Phosphorus	0.02%
Colour	Red
Pour Point	-45°C

Product Features:

- Synthetic Automatic Transmission & Power Steering Fluid.
- Offers excellent frictional stability, anti-shudder & anti-wear properties.
- For automatic transmissions and power steering systems for many European, American and Asian vehicles.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Updated: 16/07/2020 (10:16)

PSA Automobiles SA, 2-10 Boulevard de l'Europe, 78300, Poissy, France.

Tel: +33 1 61 45 45 45 www.eurorepar.com