

# **Technical Data Sheet**



Typical Inspection Data:	
Density @ 20°C	0.845 g/cm <sup>3</sup>
Viscosity @ 100°C	7.0 cSt
Viscosity @ 40°C	34 cSt
Phosphorus	0.01%
Colour	Red
Pour Point	-45°C

# ATF SSDX 3

## Oil for automatic transmission

### Specifications:

Suitable for use in applications requiring: Dexron<sup>®</sup> II, Dexron<sup>®</sup> IID, Dexron<sup>®</sup> IIE, Dexron<sup>®</sup> III

#### **Product Features:**

- Semi Synthetic Automatic Transmission Fluid.
- Protects against foaming, corrosion, oxidation and wear.
- Provides quiet and smooth gear shift.

### Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

#### Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Updated: 16/07/2020 (10:16)

PSA Automobiles SA, 2-10 Boulevard de l'Europe, 78300, Poissy, France. Tel: +33 1 61 45 45 45 www.eurorepar.com