



EUROREPAR

Technical Data Sheet



MTF FS 75W-90

Oil for manual gearboxes

Specifications:

Suitable for use in applications requiring:
Ford WSD-M2C200-C, Ford WSD-M2C200-B;
GM 1940768, GM 1940182, GM 1940764; Volvo 97309;
Volkswagen G 50; API GL-4 (75W-85), API GL-4
synthetic (75W-85 & 75W-90); Special transmission oil;
Castrol BOT 130

Product Features:

- Synthetic Manual Transmission Fluid.
- Excellent bearing and gear protection, proven synchroniser performance.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Typical Inspection Data:

Density @ 20°C	0.845 g/cm ³
Viscosity @ 100°C	16.0 cSt
Viscosity @ 40°C	100 cSt
Calcium	0.29%
Phosphorus	0.05%
Colour	Brown
Pour Point	-39°C
Brookfield Viscosity @ -40°C	110,000 cP

Updated: 16/07/2020 (10:16)

PSA Automobiles SA, 2-10 Boulevard de l'Europe, 78300, Poissy, France.

Tel: +33 1 61 45 45 45 www.eurorepar.com