

Technical Data Sheet



Typical Inspection Data: 0.845 g/cm3 Density @ 20°C Viscosity @ 100°C 11.7 cSt Viscosity @ 40°C 65 cSt Viscosity Index 177 Viscosity CCS @ -30°C 5700 cP T.B.N. 8.6 mg KOH/g Sulphated Ash Mass 0.80% Zinc 0.10% 0.17% Calcium Phosphorus 0.08% Colour Brown Flash Point 230°C Pour Point -39°C

PREMIUM 504/507 5W-30

Synthetic technology engine oil

Specifications:

ACEA C3

Meets requirements of: VW 504 00, VW 507 00; BMW LL-04; PORSCHE C30; MB 229.51

Product Features:

- · Synthetic Technology Engine Oil.
- For new generations of petrol and diesel engines, designed for vehicles fitted with post-treatment systems.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Updated: 16/07/2020 (10:16)