

Technical Data Sheet



Typical Inspection Data:	
Density @ 20°C	0.848 g/cm ³
Viscosity @ 100°C	10.6 cSt
Viscosity @ 40°C	60 cSt
Viscosity Index	168
Viscosity CCS @ -30°C	4000 cP
T.B.N.	10.0 mg KOH/g
Sulphated Ash Mass	1.1%
Zinc	0.12%
Calcium	0.26%
Phosphorus	0.10%
Colour	Brown
Flash Point	230°C
Pour Point	-36°C

PREMIUM A5/B5 5W-30

Synthetic technology engine oil

Specifications:

ACEA A5/B5; API SL/CF

Meets requirements of: Ford WSS-M2C913-A, WSS-M2C913-B, WSS-M2C913-C, WSS-M2C913-D; STJLR.03.5003

Product Features:

- Synthetic Technology Engine Oil.
- Designed for new generations of petrol and diesel engines, intended for use at extended drain Intervals.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Updated: 16/07/2020 (10:16)

PSA Automobiles SA, 2-10 Boulevard de l'Europe, 78300, Poissy, France. Tel: +33 1 61 45 45 45 www.eurorepar.com