



EUROREPAR

Technical Data Sheet



PREMIUM C3 5W-30

Synthetic technology engine oil

Specifications:

ACEA C3; API SN/CF

Meets requirements of: BMW LL-04; MB 229.31, 229.51, 229.52; VW 502 00, VW 505 01; dexos2

Product Features:

- Synthetic Technology Engine Oil.
- For new generations of petrol and diesel engines, designed for vehicles fitted with post-treatment systems.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Typical Inspection Data:

Density @ 20°C	0.850 g/cm ³
Viscosity @ 100°C	12.2 cSt
Viscosity @ 40°C	70 cSt
Viscosity Index	165
Viscosity CCS @ -30°C	6000 cP
T.B.N.	7.8 mg KOH/g
Sulphated Ash Mass	0.80%
Zinc	0.10%
Calcium	0.18%
Phosphorus	0.08%
Colour	Brown
Flash Point	230°C
Pour Point	-39°C

Updated: 16/07/2020 (10:16)

PSA Automobiles SA, 2-10 Boulevard de l'Europe, 78300, Poissy, France.

Tel: +33 1 61 45 45 45 www.eurorepar.com