



EUROREPAR

Technical Data Sheet



PROTECT GF 0W-20

Synthetic technology engine oil

Specifications:

API SN; ILSAC GF-5

Product Features:

- Synthetic Technology Engine Oil.
- High Performance.
- For modern petrol vehicles and most petrol-electric hybrids.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Typical Inspection Data:

Density @ 20°C	0.844 g/cm ³
Viscosity @ 100°C	8.5 cSt
Viscosity @ 40°C	44 cSt
Viscosity Index	174
Viscosity CCS @ -35°C	5500 cP
T.B.N.	8.5 mg KOH/g
Sulphated Ash Mass	0.80%
Zinc	0.10%
Calcium	0.13%
Phosphorus	0.08%
Colour	Brown
Flash Point	230°C
Pour Point	-36°C

Updated: 16/07/2020 (10:16)

PSA Automobiles SA, 2-10 Boulevard de l'Europe, 78300, Poissy, France.

Tel: +33 1 61 45 45 45 www.eurorepar.com