



EUROREPAR

Technical Data Sheet



SELECT 15W-40

Multigrade motor oil

Specifications:

ACEA A3/B4; API SL/CF

Suitable for use in applications requiring: VW 501 01, VW 505 00; MB 229.1

Product Features:

- Multigrade motor oil designed to provide a high level of performance and protection under most conditions.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Typical Inspection Data:

Density @ 20°C	0.865 g/cm ³
Viscosity @ 100°C	14.0 cSt
Viscosity @ 40°C	99 cSt
Viscosity Index	144
Viscosity CCS @ -20°C	4000 cP
T.B.N.	10.0 mg KOH/g
Sulphated Ash Mass	1.40%
Zinc	0.13%
Calcium	0.36%
Phosphorus	0.12%
Colour	Brown
Flash Point	230°C
Pour Point	-36°C

Updated: 16/07/2020 (10:16)

PSA Automobiles SA, 2-10 Boulevard de l'Europe, 78300, Poissy, France.

Tel: +33 1 61 45 45 45 www.eurorepar.com