



Typical Inspection Data:

Density @ 20 °C	0.845 g/cm ³
Viscosity @ 100 °C	11.7 cSt
Viscosity @ 40 °C	65 cSt
Viscosity Index	177
Viscosity CCS @ -30 °C	6000 cP
T.B.N.	8.7 mg KOH/g
Sulphated Ash Mass	0.8%
Zinc	0.10%
Calcium	0.18%
Phosphorus	0.08%
Colour	Brown
Flash Point	230 °C
Pour Point	-39 °C

Specifications:

ACEA C3, API SN
BMW LL-04; MB229.31/229.51/MB229.52;
VW 502 00, 505 01

TRADE CLUB

www.tradeclub.co.uk

VAUXHALL TRADE CLUB

C3 5W-30

Fully Synthetic Low SAPS Engine Oil

Description:

Vauxhall Trade Club C3 5W-30 is a low SAPS (Sulphated Ash, Phosphorus and Sulphur) fully synthetic, multigrade engine oil, specially formulated to meet the superior performance requirements of modern engines for both petrol and diesel applications. Vauxhall Trade Club C3 5W-30 has been developed for use in Euro IV and V compliant vehicles with DPF after-treatment devices.

Features & Benefits:

- Excellent sludge control
- Compatible with diesel particulate filters
- Low volatility

Application:

Vauxhall Trade Club C3 5W-30 is recommended for use in passenger cars and light commercial vehicles both with and without diesel particulate filters. It can be used in both petrol and diesel engines where the following specifications are required.

Health & Safety:

Please refer to the relevant health and safety data sheet. Copies are available to Trade Club members at www.tradeclub.co.uk

Part Numbers/ Pack Sizes:

- 199L – UKTOBA05
- 20L – UKTOTW05
- 5L – UKTOFL05



Created: 19/07/18
Updated: 8 March 2019 2:40 pm



VAUXHALL