VAUXHALL TRADE CLUB TECHNICAL DATA SHEET





| Typical Inspection Data: | |
|--------------------------|--------------|
| Density @ 20°C | 0.845 g/cm³ |
| Viscosity @ 100°C | 9.7 cSt |
| Viscosity @ 40°C | 50 cSt |
| Viscosity Index | 183 |
| Viscosity CCS @ -35°C | 6100 cP |
| T.B.N. | 8.0 mg KOH/g |
| Sulphated Ash Mass | 0.8% |
| Zinc | O.11% |
| Calcium | 0.19% |
| Phosphorus | 0.09% |
| Colour | Brown |
| Flash Point | >200°C |
| Pour Point | -42°C |

Specifications:

ACEA C2; FORD WSS-M2C950-A

VAUXHALL TRADE CLUB FE OW-30

Fully Synthetic Low-SAPS Engine Oil recommended for Ford petrol & diesel engines

Description:

Trade Club OW-30 FE is a fully synthetic, low-SAPS engine oil specifically designed for high fuel efficiency. It is recommended for use in Ford petrol and diesel engines from 2014 onwards.

Features & Benefits:

- · Low-SAPS engine oil
- · Designed for high fuel efficiency
- Suitable for petrol and diesel vehicles

Application:

Trade Club OW-30 FE is recommended for petrol and diesel engines. It is particularly suitable for use in Ford vehicles from 2014 onwards.

Health & Safety:

Please refer to the relevant health and safety data sheet. Copies are available to Trade Club members at www.tradeclub.co.uk

Part Numbers/ Pack Sizes:

- 199L UKTOBA13
- 20L UKTOTW13
- 5L UKTOFL13



Created: 13/06/19 Updated: 13 June 2019 3:38 pm

