VAUXHALL TRADE CLUB TECHNICAL DATA SHEET





Typical Inspection Data:	
Density @ 20 °C	0.865 g/cm³
Viscosity @ 100 °C	15.5 cSt
Viscosity @ 40 °C	95.0 cSt
Calcium	0.28%
Phosphorus	0.05%
Colour	Brown
Pour Point	-45°C

Specifications:

Ford WSD-M2C200-C, Ford WSD-M2C200-B, GM 1940768, GM 1940182, GM 1940764, Volvo 97309, Volkswagen G 50, API GL-4 (75W-85), API GL-4 synthetic (75W-85 & 75W-90), Special transmission oil, Castrol BOT 130

VAUXHALL TRADE CLUB FS 75W-90 **Fully Synthetic** Gear Oil Meeting API GL-4

Description:

Trade Club 75W-90 FS is a fully synthetic, heavy duty, multipurpose gear oil meeting the API requirements of GL-4. It is manufactured from high quality synthetic hydrocarbon base stocks with a high viscosity index and a combination of performance additives, which provide a gear lubricant designed for modern motoring conditions. Extended product life, reduced component failure and lower fuel consumption are key advantages of using this grade.

Features & Benefits:

- Outstanding oxidation stability and resistance to thermal breakdown Very high levels of wear protection
- Smoother gear change
- Long service life

Application:

Vauxhall Trade Club FS 75W-90 is recommended for highly stressed manual gearboxes, including synchromesh, in cars, vans, trucks, buses, agricultural, construction and industrial equipment.

Health & Safety:

Please refer to the relevant health and safety data sheet. Copies are available to Trade Club members at www.tradeclub.co.uk

Part Numbers/ Pack Sizes:

- 199L UKTGOB04
- 20L UKTGOT04
- 5L UKTGOF04



Created: 13/08/18 Updated: 11 January 2019 8:53 am





