

Vauxhall Trade Club C3 5W-30

Fully synthetic low SAPS engine oil

Description:

Vauxhall Trade Club C3 5W-30 is a low SAPS (Sulphated Ash, Phosphorus and Sulphur) fully synthetic, multigrade engine oil, specially formulated to meet the superior performance requirements of modern engines for both petrol and diesel applications. Vauxhall Trade Club C3 5W-30 has been developed for use in Euro IV and V compliant vehicles with DPF after-treatment devices.

Features & Benefits:

- Excellent sludge control
- Compatible with diesel particulate filters
- Low volatility

Applications:

Vauxhall Trade Club C3 5W-30 is recommended for use in passenger cars and light commercial vehicles both with and without diesel particulate filters. It can be used in both petrol and diesel engines where the following specifications are required.

Specifications & Typical Test Data:

Issuing Body	Specification	Test Description	Typical Result
ACEA	C3	Density @ 20 °C	0.850 g/cm ³
API	SN	Viscosity @ 100 °C	12.2 cSt
BMW	LL-04	Viscosity @ 40 °C	70 cSt
MB	229.31, 229.51, 229.52	Viscosity Index	165
VW	502.00, 505.01	Viscosity CCS @ -30 °C	6000 cP
		T.B.N.	6.4 mg KOH/g
		Sulphated Ash Mass	0.8%
		Zinc	0.10%
		Calcium	0.18%
		Phosphorus	0.08%
		Colour	Brown
		Flash Point	230 °C
		Pour Point	-39 °C

Health & Safety:

Please refer to the relevant health and safety data sheet.

Copies are available to Trade Club members at www.tradeclub.co.uk



Product Numbers:

199L – UKTOBA05

20L – UKTOTW05

5L – UKTOFL05