

Vauxhall Trade Club C3 5W-40

Fully synthetic low SAPS engine oil

Description:

Vauxhall Trade Club C3 5W-40 is a low SAPS (Sulphated Ash, Phosphorus and Sulphur) fully synthetic multi grade engine oil designed for use in the latest technology engines, including those fitted with exhaust gas after treatment devices. It has a broad range of applications and genuine long oil drain capabilities.

Features & Benefits:

- Effective environmental protection
- Ensures lubricant performance over extended drain intervals
- Very high standards of engine cleanliness
- Exceptional long term anti-wear and oxidation stability
- Excellent high and low temperature performance
- Exceptional long term additive response

Applications:

Vauxhall Trade Club C3 5W-40 is particularly suited to vehicles equipped with anti-pollution systems such as diesel particulate filters where its low SAPS levels will greatly prolong the lifetime of the filter. It is also ideally suited to VW PD (Pumpe Duse) engines.

Specifications & Typical Test Data:

Issuing Body	Specification	Test Description	Typical Result
ACEA	C3	Kinematic Viscosity @ 100°C (cSt)	14.1
API	SN	Kinematic Viscosity @ 40°C (cSt)	85.5
MB	229.31, 229.51	Viscosity Index	169
VW	502.00, 505.01	Flash Point COC (°C)	227
Ford	WSS-M2C917-A	Pour Point (°C)	-39
BMW	LL-04	TBN (mg KOH/g)	7.2
Porsche	A40	Sulphated Ash (% wt)	0.76
Fiat	9.55535-S2		

Health & Safety:

Please refer to the relevant health and safety data sheet.

Copies are available to Trade Club members at www.tradecub.co.uk

Product Numbers:

19L – UKTOBA09

20L – UKTOTW09

5L – UKTOFL09

