

Vauxhall Trade Club C3 5W-40

Fully synthetic low SAPS engine oil

Description:

Vauxhall Trade Club C3 5W-40 is a low SAPS (Sulphated Ash, Phosphorus and Sulphur) fully synthetic multigrade engine oil designed for use in the latest technology engines, including those fitted with exhaust gas after treatment devices. It has a broad range of applications and genuine long oil drain capabilities.

Features & Benefits:

- Ensures lubricant performance over extended drain intervals
- Very high standards of engine cleanliness
- Exceptional long term anti-wear and oxidation stability
- Excellent high and low temperature performance

Applications:

Vauxhall Trade Club C3 5W-40 is particularly suited to vehicles equipped with anti-pollution systems such as diesel particulate filters where its low SAPS levels will greatly prolong the lifetime of the filter. It is also ideally suited to VW PD (Pumpe Düse) engines.

Specifications & Typical Test Data:

Issuing Body	Specification	Test Description	Typical Result
ACEA	C3	Density @ 20 °C	0.850 g/cm ³
API	SN	Viscosity @ 100 °C	13.5 cSt
MB	229.31, 229.51	Viscosity @ 40 °C	78 cSt
VW	502.00, 505.01	Viscosity Index	160
Ford	WSS-M2C917-A	Viscosity CCS @ -30 °C	6000 cP
BMW	LL-04	T.B.N.	7.2 mg KOH/g
Porsche	A40	Sulphated Ash Mass	0.8%
		Zinc	0.10%
		Calcium	0.18%
		Phosphorus	0.09%
		Colour	Brown
		Flash Point	230 °C
		Pour Point	-39 °C

Health & Safety:

Please refer to the relevant health and safety data sheet.

Copies are available to Trade Club members at www.tradecub.co.uk

Product Numbers:

199L – UKTOBA09

20L – UKTOTW09

5L – UKTOFL09

