

# Vauxhall Trade Club C3 MX 5W-30

## Fully synthetic low SAPS engine oil

### Description:

Vauxhall Trade Club C3 MX 5W-30 is a low SAPS (Sulphated Ash, Phosphorus and Sulphur) fully synthetic, multi grade engine oil designed for use in the latest technology engines, including those fitted with exhaust gas after treatment devices. Vauxhall Trade Club C3 MX 5W-30 meets the requirements of VW Standards 504.00 and 507.00 and can be used in all current engine designs.

### Features & Benefits:

- Outstanding levels of engine cleanliness
- Long drain intervals
- Compatible with diesel particulate filters
- Low volatility

### Applications:

Vauxhall Trade Club C3 MX 5W-30 is recommended for use in passenger cars and light commercial vehicles both with and without diesel particulate filters. It can be used in both petrol and diesel engines where the following specifications are required.

### Specifications & Typical Test Data:

Issuing Body	Specification	Test Description	Typical Result
ACEA	C3	Specific Gravity @ 15°C	0.851
VW	504.00, 507.00	Kinematic Viscosity @ 100°C (cSt)	11.60
BMW	LL-04	Kinematic Viscosity @ 40°C (cSt)	71.6
MB	229.31, 229.51	Viscosity Index	160
Porsche	C30	Flash Point COC (°C)	195
		Pour Point (°C)	-40
		TBN (mg KOH/g)	5.9
		Sulphated Ash (% wt)	0.70

### Health & Safety:

Please refer to the relevant health and safety data sheet. Copies are available to Trade Club members at [www.tradeclub.co.uk](http://www.tradeclub.co.uk)

### Part Numbers:

199L – UKTOBA02

20L – UKTOTW02

5L – UKTOFL02

