

Vauxhall Trade Club C3 MX 5W-30

Fully synthetic low SAPS engine oil

Description:

Vauxhall Trade Club C3 MX 5W-30 is a low SAPS (Sulphated Ash, Phosphorus and Sulphur) fully synthetic, multigrade engine oil designed for use in the latest technology engines, including those fitted with exhaust gas after treatment devices. Vauxhall Trade Club C3 MX 5W-30 meets the requirements of VW Standards 504.00 and 507.00 and can be used in most of their engine designs.

Features & Benefits:

- Outstanding levels of engine cleanliness
- Long drain intervals
- Compatible with diesel particulate filters
- Low volatility

Applications:

Vauxhall Trade Club C3 MX 5W-30 is recommended for use in passenger cars and light commercial vehicles both with and without diesel particulate filters. It can be used in both petrol and diesel engines where the following specifications are required.

Specifications & Typical Test Data:

Issuing Body	Specification	Test Description	Typical Result
ACEA	C3	Density @ 20 °C	0.850 g/cm ³
VW	504.00, 507.00	Viscosity @ 100 °C	11.7 cSt
BMW	LL-04	Viscosity @ 40 °C	68 cSt
MB	229.31, 229.51	Viscosity Index	170
Porsche	C30	Viscosity CCS @ -30 °C	5700 cP
		T.B.N.	8.6 mg KOH/g
		Sulphated Ash Mass	0.8%
		Zinc	0.10%
		Calcium	0.17%
		Phosphorus	0.09%
		Colour	Brown
		Flash Point	230 °C
		Pour Point	-39 °C

Health & Safety:

Please refer to the relevant health and safety data sheet. Copies are available to Trade Club members at www.tradeclub.co.uk

Part Numbers:

199L – UKTOBA02

20L – UKTOTW02

5L – UKTOFL02

