

TECHNICAL DATA SHEET

Vauxhall Trade Club FS 5W-40

Fully synthetic passenger car engine oil

Description:

Vauxhall Trade Club FS 5W-40 is a fully synthetic, multigrade engine oil specially formulated to offer long term durability and engine protection in a wide variety of conditions. It is recommended for use in petrol and diesel engines in passenger cars and vans where its advanced additive technology provides significant benefits.

Features & Benefits:

- Excellent anti-wear protection
- Long drain intervals
- Excellent low temperature fluidity
- Outstanding levels of engine cleanliness

Applications:

Vauxhall Trade Club FS 5W-40 is recommended for the latest petrol and diesel engines, including turbocharged and supercharged versions, in passenger cars and light commercial vehicles. It is recommended where any of the following specifications and a 5W-40 viscosity grade are required.

Specifications & Typical Test Data:

Issuing Body	Specification	Test Description	Typical Result
API	SL	Specific Gravity @ 15°C	0.860
APEA	A3/B3, A3/B4	Kinematic Viscosity @ 100°C (cSt)	14.65
VW	502.00, 505.00	Kinematic Viscosity @ 40°C (cSt)	91.5
MB	229.3	Viscosity Index	168
BMW	Longlife-98	Flash Point COC (°C)	205
Renault	RN0700, RN0710	Pour Point (°C)	-35
		TBN (mg KOH/g)	9.10

Health & Safety:

Please refer to the relevant health and safety data sheet.

Copies are available to Trade Club members at www.tradeclub.co.uk

Part Numbers:

199L – UKTOBA07

20L – UKTOTW07

5L – UKTOFL07

