Vauxhall Trade Club SS 10W-40

Semi-synthetic passenger car engine oil

Description:

Vauxhall Trade Club SS 10W-40 is manufactured from high quality base fluids and a carefully balanced additive system.

This grade is suitable for use in petrol and diesel engines fitted to passenger cars and light commercial vehicles. Vauxhall Trade Club SS 10W-40 provides a high level of engine cleanliness and controls high temperature deposits, especially in turbocharged units. This grade will protect critical components, such as camshafts, valve gear and bearings from wear and ensures overall protection from rust and corrosion.

Features & Benefits:

- High level of engine cleanliness
- Superior anti-wear performance
- Excellent corrosion protection

Applications:

Vauxhall Trade Club SS 10W-40 is suitable for use in passenger cars and light commercial vehicles. It can be used in both petrol and diesel engines where the following specifications are required.

Issuing Body	Specification	Test Description	Typical Result
ACEA	A3/B4	Density @ 20 °C	0.865 g/cm ³
API	SL	Viscosity @ 100 °C	13.7 cSt
		Viscosity @ 40 °C	92 cSt
		Viscosity Index	155
		Viscosity CCS @ -25 °C	6400 cP
		T.B.N.	10.0 mg KOH/g
		Sulphated Ash Mass	1.3%
		Zinc	0.13%
		Calcium	0.12%
		Phosphorus	0.11%
		Colour	Brown
		Flash Point	230 °C
		Pour Point	-39 °C

Specifications & Typical Test Data:

Health & Safety:

Please refer to the relevant health and safety data sheet. Copies are available to Trade Club members at www.tradeclub.co.uk



