

Vauxhall Trade Club SS 5W-30

Semi-synthetic motor oil recommended for Zetec engines

Description:

Vauxhall Trade Club SS 5W-30 is a semi-synthetic, multi grade engine oil, specially formulated to meet the superior performance and fuel efficiency requirements of modern engines requiring low viscosity oils. Enhanced oil flow and film strength give essential protection during start-up, and advanced additive technology provides long term benefits including reduced wear on critical components.

Features & Benefits:

- Fuel efficient multi grade formulation
- High thermal stability
- Excellent low temperature fluidity
- Outstanding engine protection

Applications:

Vauxhall Trade Club SS 5W-30 is recommended for petrol and diesel engines in passenger cars and light commercial vehicles. It is particularly suitable for use in Zetec and Duratorq engines fitted to many Ford vehicles as well as other manufacturers such as Land Rover. It is recommended where any of the following specifications and a 5W-30 viscosity grade are required.

Specifications & Typical Test Data:

Issuing Body	Specification	Test Description	Typical Result
ACEA	A1/B1	Specific Gravity @ 15°C	0.874
API	SL	Kinematic Viscosity @ 100°C (cSt)	10.6
Ford	WSS-M2C913-B WSS-M2C913-A	Kinematic Viscosity @ 40°C (cSt)	64.6
		Viscosity Index	163
		Flash Point COC (°C)	200
		Pour Point (°C)	-39
		TBN (mg KOH / g)	8.95

Health & Safety:

Please refer to the relevant health and safety data sheet.

Copies are available to Trade Club members at www.tradeclub.co.uk

Product Numbers:

199L – UKTOBA06

20L – UKTOTW06

5L – UKTOFL06

