

Vauxhall Trade Club FS 75W-90

Fully synthetic gear oil meeting API GL-5

Description:

Vauxhall Trade Club FS 75W-90 is a fully synthetic, heavy duty, multipurpose gear oil meeting the API requirement of GL-5. It is manufactured from high quality synthetic hydrocarbon base stocks with a high viscosity index and a combination of performance additives, which provide a gear lubricant designed for modern motoring conditions. Extended product life, reduced component failure and lower fuel consumption are key advantages of using this grade.

Features & Benefits:

- Reduced fuel consumption
- Outstanding oxidation stability and resistance to thermal breakdown
- Very high levels of wear protection
- Smoother gear change
- Long service life

Applications:

Vauxhall Trade Club FS 75W-90 is recommended for highly stressed manual gearboxes, including synchromesh, in cars, vans, trucks, buses, agricultural, construction and industrial equipment.

Specifications & Typical Test Data:

Issuing Body	Specification	Test Description	Typical Result
API	GL-5	Appearance	Clear Liquid Yellow
MIL	2105D	Specific Gravity @ 15°C	0.866
MAN	342 Type 1	Kinematic Viscosity @ 100°C (cSt)	15.3
MB	235.0	Kinematic Viscosity @ 40°C (cSt)	98.5
Volvo	97310, 97316	Viscosity Index	164
		Flash Point COC (°C)	225
		Pour Point (°C)	-45

Health & Safety:

Please refer to the relevant health and safety data sheet.

Copies are available to Trade Club members at www.tradeclub.co.uk

Part Numbers:

199L - UKTOGB04

20L - UKTOGA04

5L - UKTOGF04

