

Vauxhall Trade Club C2 5W-30

Fully synthetic low SAPS engine oil

Description:

Vauxhall Trade Club C2 5W-30 is a low SAPS (Sulphated Ash, Phosphorus and Sulphur) fully synthetic, multi grade engine oil, specially formulated to meet the superior performance and fuel efficiency requirements of modern engines that require low viscosity oils for petrol and diesel applications. Vauxhall Trade Club C2 5W-30 has been developed for use in Euro IV and V compliant vehicles with DPF after treatment devices.

Features & Benefits:

- Improved fuel economy benefits
- Excellent sludge control
- Compatible with diesel particulate filters
- Low volatility

Applications:

Vauxhall Trade Club C2 5W-30 is recommended for use in passenger cars and light commercial vehicles both with and without diesel particulate filters. It can be used in both petrol and diesel engines where the following specifications are required.

Specifications & Typical Test Data:

Issuing Body	Specification	Test Description	Typical Result
ACEA	C2	Specific Gravity @ 15°C	0.854
API	SN	Kinematic Viscosity @ 100°C (cSt)	10.30
PSA	B712290	Kinematic Viscosity @ 40°C (cSt)	60.8
Fiat	9.55535-S1	Viscosity Index	161
		Flash Point COC (°C)	195
		Pour Point (°C)	-40
		TBN (mg KOH / g)	7.3
		Sulphated Ash (% wt)	0.79

Health & Safety:

Please refer to the relevant health and safety data sheet. Copies are available to Trade Club members at www.tradeclub.co.uk

Product Numbers:

199L – UKTOBA03
 20L – UKTOTW03
 5L – UKTOFL03

