TECHNICAL DATA SHEET

Vauxhall Trade Club C2 5W-30

Fully synthetic low SAPS engine oil

Description:

Vauxhall Trade Club C2 5W-30 is a low SAPS (Sulphated Ash, Phosphorus and Sulphur) fully synthetic, multi grade engine oil, specially formulated to meet the superior performance and fuel efficiency requirements of modern engines that require low viscosity oils for petrol and diesel applications. Vauxhall Trade Club C2 5W-30 has been developed for use in Euro IV and V compliant vehicles with DPF after treatment devices.

Features & Benefits:

- · Improved fuel economy benefits
- Excellent sludge control
- · Compatible with diesel particulate filters
- Low volatility

Applications:

Vauxhall Trade Club C2 5W-30 is recommended for use in passenger cars and light commercial vehicles both with and without diesel particulate filters. It can be used in both petrol and diesel engines where the following specifications are required.

Specifications & Typical Test Data:

Issuing Body	Specification	Test Description	Typical Result
ACEA	C2	Density @ 20 °C	0.850 g/cm ³
API	SN	Viscosity @ 100 °C	10.3 cSt
PSA	B71 2290	Viscosity @ 40 °C	58 cSt
		Viscosity Index	169
		Viscosity CCS @ -30 °C	5500 cP
		T.B.N.	7.0 mg KOH/g
		Sulphated Ash Mass	0.7%
		Zinc	0.09%
		Calcium	0.19%
		Phosphorus	0.08%
		Colour	Brown
		Flash Point	230 °C
		Pour Point	-36 °C

Health & Safety:

Please refer to the relevant health and safety data sheet. Copies are available to Trade Club members at www.tradeclub.co.uk

Product Numbers:

199L – UKTOBA03 20L – UKTOTW03 5L – UKTOFL03

